

centos bonding Active



image.png

perplexity AI

Bonding Active

1. eth0 eth1 eth0

```
[root@localhost ~]# cat /proc/net/bonding/bond0
Ethernet Channel Bonding Driver: v3.7.1 (April 27, 2011)

Bonding Mode: fault-tolerance (active-backup)
Primary Slave: None
Currently Active Slave: eth1
MII Status: up
MII Polling Interval (ms): 100
Up Delay (ms): 0
Down Delay (ms): 0

Slave Interface: eth0
MII Status: up
Speed: 1000 Mbps
Duplex: full
Link Failure Count: 0
Permanent HW addr: 00:00:00:00:00:00
Slave queue ID: 0

Slave Interface: eth1
MII Status: up
Speed: 1000 Mbps
```

```
Duplex: full
Link Failure Count: 0
Permanent HW addr: 00:00:00:00:00:01
Slave queue ID: 0
```

2. bond0[] [] [] eth1 -> eth0

```
[root@localhost ~]# ifenslave -c bond0 eth0
[root@localhost ~]# cat /proc/net/bonding/bond0
Ethernet Channel Bonding Driver: v3.7.1 (April 27, 2011)

Bonding Mode: fault-tolerance (active-backup)
Primary Slave: None
Currently Active Slave: eth0
MII Status: up
MII Polling Interval (ms): 100
Up Delay (ms): 0
Down Delay (ms): 0

Slave Interface: eth0
MII Status: up
Speed: 1000 Mbps
Duplex: full
Link Failure Count: 0
Permanent HW addr: 00:00:00:00:00:00
Slave queue ID: 0

Slave Interface: eth1
MII Status: up
Speed: 1000 Mbps
Duplex: full
Link Failure Count: 0
Permanent HW addr: 00:00:00:00:00:01
Slave queue ID: 0
```

Revision #4

Created 2022-06-07 07:20:47 KST by artop0420

Updated 2026-02-02 02:04:47 KST by artop0420