

[[[NIC eth0, eth1 [[[[[[br0 [[bridge [[[[.

1. Bridge Device [[

```
# vi /etc/sysconfig/network-script/ifcfg-br0
DEVICE=br0
ONBOOT=on
TYPE=Bridge
BOOTPROTO=static
IPADDR=192.168.1.2
NETMASK=255.255.255.0
USRCTL=no
```

2. [[Device [[

#eth0 [[[[[[

```
$ vi /etc/sysconfig/network-script/ifcfg-eth1
DEVICE=eth1
ONBOOT=yes
BOOTPROTO=none
BRIDGE=br0
USRCTL=no
```

#eth1 [[[[[[

```
$ vi /etc/sysconfig/network-script/ifcfg-eth1
DEVICE=eth1
ONBOOT=yes
BOOTPROTO=none
BRIDGE=br0
USRCTL=no
```

3. ip_forward [[

```
$ vi /etc/sysctl.conf
net.ipv4.ip_forward = 1
```

4. Bridge

```
$ brctl show
```

```
bridge name      bridge id          STP enabled      interfaces
br0              8000.0800271b0b5f  no              eth1
                                                         eth0
```

Revision #2

Created 2022-06-07 14:13:55 KST by artop0420

Updated 2026-01-28 22:45:44 KST by artop0420