

1. Sendmail [] []

```
$> yum erase sendmail -y
```

2. Postfix [] []

```
$> yum install postfix -y
```

3. Postfix []

```
vi /etc/postfix/main.cf

mydomain = localhost ( [ ] [ ] [ ] [ ] )
mynetworks_style = host ( [ ] [ ] [ ] [ ] [ ] )
mynetworks = 127.0.0.1, 192.168.0/24 ( [ ] [ ] [ ] [ ] )
smtpd_sasl_auth_enable = yes ( [ ] [ ] [ ] [ ] [ ] )
inet_interfaces = $myhostname (open relay [ ] [ ] [ ] all [ ] [ ] )
postfix, [ ] [ ] [ ] [ ] [ ] [ ]
```

```
$> vi /usr/lib/sasl2/smtpd.conf

pwcheck_method: saslauthd
chkconfig postfix on
chkconfig saslauthd on
/etc/init.d/postfix start
/etc/init.d/saslauthd start
```

4. [] [] Trouble Shooting

1. [] [] []

1. postfix [] [] [] : /var/spool/postfix
2. incoming : [] [] []
3. active : [] [] [] [] []
4. deferred : [] [] [] [] []
5. corrupt : [] [] [] [] []

2. [] [] []

1. [] [] [] [] sendmail [] [] [] /var/log/maillog [] []

2. `maildir` /var/spool/mail/`maildir`

3. Queue

```
[root@localhost ~]# mailq -> Queue
[root@localhost ~]# postfix flush -> Queue
[root@localhost ~]# postsuper -d ALL deferred -> Queue Deferred

```

1. `main.cf` `virtual`

```
$> vi /etc/postfix/main.cf
virtual_alias_domain = test.com example.com
```

2. Alias

```
$> vi /etc/postfix/main.cf
virtual_alias_maps = hash:/etc/postfix/virtual
```

```
$> vi /etc/postfix/virtual
postmaster@example.com postmaster
info@example.com joe
sales@example.com jane

```

3. `postmap`

```
[root@localhost ~]# postmap /etc/postfix/virtual
```

Revision #3

Created 2022-06-08 06:32:46 KST by artop0420

Updated 2026-03-12 00:17:33 KST by artop0420