

podman?? ?????? ?????? ???
?????




```
$> podman info
...
ociRuntime:
  name: runc
  package: runc-1.1.12-1.module+el8.10.0+1825+623b0c20.x86_64
  path: /usr/bin/runc
...
```

2. DOCKER

```
$> docker info
...
ociRuntime:
  name: crun
  package: crun-1.8.7-1.el9.x86_64
  path: /usr/bin/crun
...
```

3. runtime

1. crun runc 2 , 50
2. crun , rootless , OCI stdout/stderr

????

1. 1 , 2 , 3)
2. podman

```
$> yum update podman -y
...
```

3. podman security

```
$> podman run -d --security-opt=seccomp=unconfined --name=test
...
```

4. runtime `crun`

```
$> podman run --runtime crun -d --name=test ...
```

????

```
$> docker ps -a
```

Emulate Docker CLI using podman. Create `/etc/containers/nodocker` to quiet msg.

CONTAINER ID	IMAGE	COMMAND	CREATED
STATUS	PORTS	NAMES	
bd3896eb439d	localhost:5000		5 months ago
ago	0.0.0.0:80->80/tcp	test	Up 2 weeks

Reference

1. https://docs.redhat.com/ko/documentation/red_hat_enterprise_linux/9/html/building_running_and_managing_containers/selecting-a-container-runtime_building-running-and-managing-containers#selecting-a-container-runtime_building-running-and-managing-containers
2. https://docs.redhat.com/ko/documentation/red_hat_enterprise_linux/8/html/building_running_and_managing_containers/proc_running-containers-with-runc-and-crun_selecting-a-container-runtime

Revision #8

Created 2023-07-13 00:29:37 KST by artop0420

Updated 2026-03-11 00:02:41 KST by artop0420