

oracle 10g ????? ?? ??

1. 检查 数据库 状态

```
SQL> archive log list
\\Database log mode          No Archive Mode
Automatic archival          Disabled
Archive destination         USE_DB_RECOVERY_FILE_DEST
Oldest online log sequence  1
Current log sequence        2
\\SQL> show parameter spfile
\\NAME                        TYPE        VALUE
-----
spfile                        string      /u01/app/oracle/product/10.2.0
                               /db_1/dbs/spfileTSH1.ora
```

2. 修改 数据库 参数

```
SQL> ALTER SYSTEM SET log_archive_dest_1='location=/u01/app/oracle/oradata/data reope
n=60' scope=spfile;
System altered.
\\SQL> ALTER SYSTEM SET log_archive_format='%t_%s_%r.arc' scope=spfile;
System altered.
```

3. Oracle 关闭

```
SQL> shutdown immediate
Database closed.
Database dismounted.
ORACLE instance shut down.
```

4. Oracle 启动

```
SQL> startup mount
.ORACLE instance started.
\\Total System Global Area 608174080 bytes
```

```
Fixed Size          1220844 bytes
Variable Size       171970324 bytes
Database Buffers    432013312 bytes
Redo Buffers        2969600 bytes
Database mounted.
```

5. log 1 1

```
SQL> alter database archivelog;
Database altered.
```

6. 1 1 1 1 1 1 1 1 1 1

```
SQL> archive log list
Database log mode          Archive Mode
Automatic archival        Enabled
Archive destination       /u01/app/oracle/oradata/data
Oldest online log sequence 1
Next log sequence to archive 2
Current log sequence      2
```

7. DB Open

```
SQL> alter database open;
Database altered.
```

8. DB 1 1 & Cold Backup 1 1

```
SQL> shutdown immediate
Database closed.
Database dismounted.
ORACLE instance shut down.
```

9. log 1 1 1 1

```
SQL> ALTER SYSTEM SWITCH LOGFILE;
\\System altered.
```

Revision #1

Created 2022-06-06 17:13:02 KST by artop0420

Updated 2022-06-08 04:01:09 KST by artop0420