

04. Openstack cli ??

keystone ??

```
[root@openstackdev-1 ~]# . ~/keystonerc_admin
[root@openstackdev-1 ~(keystone_admin)]#
```

??? ?????

```
~(keystone_admin)]# openstack image create \
--disk-format qcow2 \
--file CentOS-7-x86_64-GenericCloud-2009.qcow2 \
--public\
Centos7-2009
```

CentOS-7-x86_64-GenericCloud-2009.qcow2 qcow2 ,
Centos7-2009,

???? ??

1.

```
~(keystone_admin)]# openstack server create \
--flavor m1.small \
--image Centos7-2009 \
--network private \
--boot-from-volume 30 \
--key-name ssh \
--wait \
--max 5 \
client
```

flavor m1.small , Centos7-2009, private
, 30G client-{n} 5

2. ????? ????? ??? ??

```
~(keystone_admin)]# openstack server list --all-projects
+-----+-----+-----+
+-----+-----+-----+
| ID                | Name          | Status |
Networks           | Image         | Flavor |
+-----+-----+-----+
+-----+-----+-----+
| 3d728b9b-7c87-4369-8036-ab143af9eb31 | client-2      | ACTIVE |
private=192.168.20.177          | N/A (booted from volume) | m1.small |
| 5427d961-2b6b-4804-85df-c275eddf8e2d | client-3      | ACTIVE |
private=192.168.20.109          | N/A (booted from volume) | m1.small |
| ab7ea5fa-133f-4e10-b5fa-874c4f943720 | client-4      | ACTIVE |
private=192.168.20.115          | N/A (booted from volume) | m1.small |
| cc0974ed-187a-4a19-8a6a-484d477b83c1 | client-1      | ACTIVE |
private=192.168.20.122          | N/A (booted from volume) | m1.small |
| a7e51fdd-cecb-436f-9224-8d1e5d02be28 | ubuntu_sample | ACTIVE |
private=192.168.20.125          | N/A (booted from volume) | m1.small |
+-----+-----+-----+
+-----+-----+-----+
```

3. ????? ?? (?? ????? ??? ??? ??? ?)

```
~(keystone_admin)]# openstack server delete client-1 client-2
```

Revision #2

Created 2022-07-23 16:48:21 KST by artop0420

Updated 2023-12-24 02:49:01 KST by artop0420